

Work Permit # DRL-2006-002
Work Order # ____
Job# ____ Activity# ____

ork requester fills out this section.		ork Permit				
Requester: Don Lynch	Date: 4/17/2006	Ext.: 2253	Dept/Div/Group: PO/PHE	NIX		
Other Contact person (if different from req	uester): Sal Marino		Ext.: 3704			
Control Coordinator: Don Lynch Start Date: 4/19/2006 E		Est. End Date: 4/30/2006	Est. End Date: 4/30/2006			
rief Description of Work: Install HBD Pro	ototype in IR					
	Room: IR	Equipment: n/a	Service Provider: PHENI	X Techs		
Requester/Designee, Service Provide	r, and ES&H (as necessary) fill out		rsis			
ES&H ANALYSIS						
Radiation Concerns	None	Airborne	Contamination	⊠Radiation		
		·	Soil Density Gauges	X-ray Equipment		
Special nuclear materials involved, r				ed, notify Laboratory Criticality Officer		
Safety Concerns	□ None	☐ Ergonomics	☐ Transport of Haz/Rad Materi	• • •		
•	☐ Confined Space*	Explosives	Lead*	☐ Penetrating Fire Walls		
☐ Adding/Removing Walls or Roofs	Corrosive	☐ Flammable	☐ Magnetic Field*	☐ Pressurized Systems		
☐ Asbestos*	☐ Cryogenic	☐ Fumes/Mist/Dust*	☐ Material Handling	Rigging/Critical Lift		
Beryllium*	☐ Electrical	☐ Heat/Cold Stress	☐ Noise*	☐ Toxic Materials*		
☐ Biohazard*	☐ Elevated Work*	☐ Hydraulic	☐ Non-ionizing Radiation*	☐ Vacuum		
Chemicals*	☐ Excavation	☐ Lasers*	Oxygen Deficiency*	Other UV Lamp		
* Does this work require medical clearan	–	<u> </u>		<u> </u>		
Environmental Concerns		None None	☐ Work impacts Environmenta	I Permit No		
		 	Soil			
Atmospheric Discharges (rad/non-ra	id)	☐ Land Use	Activation/contamination	☐ Waste-Mixed		
☐ Chemical or Rad Material Storage of	r Use	☐ Liquid Discharges	☐ Waste-Clean	☐ Waste-Radioactive		
Cesspools (UIC)		☐ Oil/PCB	☐ Waste-Hazardous	☐ Waste-Regulated Medical		
_ ' ' '		Management				
High water/power consumption		☐ Spill potential	☐ Waste-Industrial	☐ Underground Duct/Piping		
Waste disposition by:				☐ Other		
Pollution Prevention (P2)/Waste Minim		None ☐ Yes				
FACILITY CONCERNS	None Non					
☐ Access/Egress Limitations	☐ Electrical Noise	☐ Potential to Cause a F		☐ Vibrations		
	☐ Impacts Facility Use Agree		☐ Temperature Change	☐ Other		
Configuration Control	☐ Maintenance Work on Ven	tilation Systems	☐ Utility Interruptions			
WORK CONTROLS						
Work Practices						
None	Exhaust Ventilation	Lockout/Tagout	☐ Spill Containment	Security (see Instruction Sheet)		
☐ Back-up Person/Watch	☐ HP Coverage	☐ Posting/Warning Signs	☐ Time Limitation	Other: Magnet Operational Lockout and survey		
Barricades	☐ IH Survey	☐ Scaffolding-requires inspection	☐ Warning Alarm (i.e. "high lev	rel")		
Protective Equipment						
None	☐ Ear Plugs	Gloves	☐ Lab Coat	☐ Safety Glasses		
Coveralls	☐ Ear Muffs	Goggles	Respirator	☐ Safety Harness		
☐ Disposable Clothing	☐ Face Shield	☐ Hard Hat	☐ Shoe Covers	Shoes		
Permits Required (Permits must be valid	d when job is scheduled.)					
None Non	Cutting/Welding	☐ Impair Fire Protection	Systems			
☐ Concrete/Masonry Penetration	☐ Digging/Core Drilling	Rad Work Permit-RWF				
☐ Confined Space Entry	☐ Electrical Working Hot	Other				
Dosimetry/Monitoring						
None Non	☐ Heat Stress Monitor	Real Time Monitor	☐ TLD			
☐ Air Effluent	☐ Noise Survey/Dosimeter	Self-reading Pencil	☐ Waste Characterization			
Ground Water	O ₂ /Combustible Gas	Self-reading Digital Dosimeter	☐ Other			
☐ Liquid Effluent	☐ Passive Vapor Monitor	☐ Sorbent Tube/Filter				
·	<u> </u>	Pump				
Training Requirements (List below specifications) PHENIX Awareness, CA Access	cinc training requirements)					
			If using the permit when all ha	zard ratings are low, only the following		
Based on analysis above, the Walkdoratings below:	wn Team determines the risk, com	plexity, and coordination		ed, there is no need to use back of		
ES&H Risk Level:	✓ Low	High	WCC:	Date:		
Complexity Level:		☐ High	Service Provider:	Date:		
Work Coordination:		☐ High	Authorization to start	Date:		
oomanadon	Nioderate	<u> </u>	/Departmental Con/MCC/Design	Date.		

Work Plan (procedures, timing	g, equipment, and personnel availability nee	ed to be addressed):					
Special Working Conditions Re	equired:						
Operational Limits Imposed:							
Post Work Testing Required:							
Job Safety Analysis Required: ☐ Yes ☐ No			Walkdown Required: ☐ Yes ☐ No				
Reviewed by: Primary Review	ver will determine the size of the review tear	n and the other sign:	atures required ba	ased on hazards	and job complexit	v Primary Reviewer signature mea	
that the hazards and risks that	could impact ES&H have been identified an	d will be controlled a	according to BNL	requirements.	rana job complexit	Г	
<u>Title</u>	Name (print)	<u>Signature</u>		Life #		<u>Date</u>	
Primary Reviewer							
ES&H Professional							
Other							
Other							
Work Control Coordinator							
Service Provider							
	Review Done: in series	☐ team					
		1					
site personnel fill out this sec							
	onnel performing work have read and under	rstand the nazards a			any attachments).		
Job Supervisor:			Contractor Supervisor:				
Workers:	Life#:		Workers :		Life#:		
Workers are encouraged to pro	ovide feedback on ES&H concerns or on idea	as for improved job	work flow. Use fe	edback form or	space below.		
nartmental Joh Sunanciaer Wa	ork Control Coordinator/Designee						
	tart work: (Permit has been reviewed, work	controls are in place	e and site is ready	/ for iob.)			
Name:	Signature:				Date:	e.	
	o.g.ra.aror		1 244		24.0.	<u></u>	
	ork Requester/Designee determines if Pos	st Job Review is re	quired. Yes	☐ No			
Post Job Review (Fill in names	of reviewers)						
Name:	Signature:		Life#:		Date:	Date:	
Name:	Signature:		Life#: Date		Date:		
orker provides feedback.							
Worker Feedback (use attache							
a) WCM/WCC: Is any feedbac	ck required? Yes No						
b) Warkers: Are there better n	nethods or safer ways to perform this job in	the future? Yes	i □ No				
b) Workers. Are there better h							
, , , , , , , , , , , , , , , , , , ,	tor (authorizing dent) checks quality of	completed permit a	nd ensures the	work site is left	in an accentable	condition (WCC can delegate	
, , , , , , , , , , , , , , , , , , ,	tor (authorizing dept.) checks quality of o	completed permit a	nd ensures the \	work site is left	in an acceptable	condition. (WCC can delegate	
seout: Work Control Coordina		completed permit a	nd ensures the v	work site is left	in an acceptable Date:	condition. (WCC can delegate	

- I. Prototype Installed in test setup position (cradle position on lift table)
 - a. Prepare gas system for installation of HBD (flow CF4 at a flow rate of 10 l/min for at least 4 hours prior to installation of prototype. (Note: Operating flow rate is $\sim 1.5 \text{ l/min}$.)
 - b. Receive prototype as delivered from Stony Brook at PHENIX
 - c. Disconnect transport gas bottle and cap ports.
 - d. Verify that PHENIX magnets are locked out of operation
 - e. Open west carriage for access to CM region.
 - f. Partially deflate helium bags as necessary to allow for access to gas lines and/or as needed to remove BLM test setup and position prototype on lift table.
 - g. Disconnect and remove complete BLM test setup.
 - h. Install 3 way purge valves on HBD inlet and outlet lines.
 - Carry prototype to CM region in path practiced with mockup (through plug door, east of EC, south of MMS, handling gently over crates on south end of west carriage into CM region and over BB crate onto lift table.
 - j. Orient prototype such that window of detector faces beampipe. (see figure)
 - k. Install UV lamp and power supply on upper surface of installed detector. Secure both to the HBD prototype mounting structure and secure structure to the lift table.
 - 1. Attach supply and return piping, purge supply and return lines using 3 way valves and establish flow to detector.
 - m. Attach HV and signal cables and secure cables in cable trays.
 - n. Perform magnet surveys if and as required by CA cognizant engineer(s).
 - o. Reinflate He bags.
 - p. Electrical/operational checkout tests per plan.
- II. Prototype Installed in run position (upright on I-beams, around beampipe)
 - a. Partially deflate He bags as necessary to allow HBD prototype to be installed in operation position (on HBD I-beams around beampipe.)
 - b. Disconnect and remove UV lamp and power supply from prototype, remove from IR and return equipment to HBD group.
 - Disassemble HBD prototype from test setup support structure and install run position support structure.
 - d. If necessary disconnect supply and return lines and/or HV and signal cables from HBD prototype and cap ports.
 - e. Install HBD prototype in run position.
 - f. Reattach and/or reroute gas supply and return lines and HV and signal cables to HBD prototype and secure/strain relief lines and cables as necessary to support structure and cable trays.
 - g. Electrical/operational checkout tests per plan.

Notes:

- 1. Radiation concerns: The HBD prototype detector contains a radioactive Fe_{55} source with a 5 μ Cu source (rated approximately 2 years ago). This is below the control level and as such requires no special procedures.
- 2. The HBD prototype utilizes an external UV lamp and power supply for test/calibration of the prototype detector. This lamp is operated only when the IR is closed and interlocked, thus posing no hazard to personnel. The power supply contains some ferromagnetic metal components and therefore may require magnetic survey. These components will be rigifly secured to the HBD

prototype mounting structure. CA cognizant engineer(s) will be notified to allow for appropriate survey/tests after installation is completed.



Figure 1. HBD in test Setup position.




Figure 2: HBD in Run position.